



## PRODUCT DATA SHEET

# GLASS FABRIC

850

STANDARD DIAMOND PATTERN, PRE-PAINTED,  
155 GR/M<sup>2</sup>

<b>Product composition</b>	Glass-tensioned fabric (type E and C), pre-treated with a starch polymer coating.
<b>Colour/ Glass level</b>	White, mate.
<b>Characteristics</b>	<p>Waterproof, resistant and chemically inert and therefore cannot be affected by rot.</p> <p>Absorption of water (vapour) is almost not possible. Vapor permeable/ open, toxicologically harmless, dimensionally stable, abrasive bridging (if treated with a suitable coating system) surface reinforcement.</p>
<b>Measurements and weight</b>	Roll length 25 or 50 meters x 1m wide. 155 gr/m <sup>2</sup> (± 5 gr/m <sup>2</sup> ).
<b>Packaging</b>	Fitted with matching closing paper edge protectors (crowns) shrink-wrapped, packed in a pallet box (individual carton packaging on request).
<b>Application</b>	Surface reinforcing fabric for a paint system. Promotes the surface structure, hairline over-bridging. Ideal as a stable base for decorative wall techniques.
<b>Transport/ storage</b>	Dry and protected against moisture/ vapors. Max RH 75% at min. 8°C.
<b>Substrate</b>	The substrate must be clean, dry, dimensionally stable. In accordance with standard DIN 1,8363 §3. Highly absorbent substrates should be pre-treated with an impregnation (in accordance with manufacturer's writing diluted, usually 1:3 with water). Q2/Q3 subground requirement with regard to structural irregularities-plain.

NOTE: the substrate must still be used after treatment absorbent, so NOT CLOSED.

**Instructions**

Glass fabric can be used on all indoor wallpaperable surfaces. Provide a dry, clean, grease-free and smooth surface.

Pre-treat highly absorbent substrates first. Remove old wallpaper and non-adherent paint layers thoroughly. Use only prescribed adhesive: DWD Glasfacoll 210 and 220. Warranty applies only when using the prescribed adhesive. Follow further instructions on the adhesive packaging. Glue glass fabric perpendicular. Press the strokes with a rubber roller or a wallpaper spatula, so there will not appear any bubbles under.

For ceilings, skirting boards, windows, frames, etc., press the glass fabric with a wallpaper spatula into the corner and cut with a sharp knife. Do not overlap the wallpaper while gluing. Remove adhesive stains immediately with a sponge and clean water. Wipe dry with a clean dry cloth.

**Paintable**

After drying, the glass fabric can be painted over with any quality wall paint. Follow the paint manufacturer's instructions.

**WHC**

0 pollution/ harmful to the water/ environment (standard from 0 to 3.0 no danger).

**Fire classification**

Fire classification		Smoke formation	Droplet Formation
B		S1	D0

B-s1, d0

**Processing of residual waste**

To be treated as household waste, construction waste, mineral waste.

**Advice**

Check the fabric before processing. Woven glass is a natural product that should have an irregular structure. The processing of material from the same batch is advised for this reason. Claims of more than 3 strokes will NOT BE ACCEPTED.

**Note**

The specifications may reasonably deviate. The dates are not calibrated for specification purposes. Product data will be periodically be updated, under and while preserving resource base material and process developments.

This technical information is based on the latest available technology.

We guarantee the consistent high quality of our products and our deliveries/ other services. The degree of diversity of applications in

the processing of our products, is also the extent to which we have no influence on these processes, this leaves excluded/ extended warranties on our products recognize after these processes.

If a new version becomes available, it loses Technical Data Sheet it is validity.

#### CAUTION

The information, as specified in this production data sheet, is based on accurate laboratory tests and available practical experience. The information is not binding, which generally also applies to any practical technical support, verbal or written, given the wide variety of applications and uses, including those of third parties, we cannot take any responsibility. Analysis results and all information regarding the condition and stability of our products are guidelines only with no obligation on our part unless specifically in writing given. They are also no guarantee for specific properties. We advise that the customer determines the suitability of our products, with the regard to the intended application and technique used by extensive testing. In addition to the above, are our General sales. Delivery and payment conditions apply.

Alblasserdam, July 2023

Dutch Wall Decor bv, Ohmweg 1F, (NL) 2952 BD Alblasserdam

[www.dwd.nu](http://www.dwd.nu)